



DESCRIPTION :


1.5 Pair 22 AWG Shielded RS-485 Communication Cable, Stranded Tinned copper conductors with PE insulation, overall braided shield, Stable signal transmission, EMI protection for indoor control & Industrial automation systems.

APPLICATION :

Suitable for RS-485, BACnet, Modbus RTU, and DMX control systems, panel wiring, BMS and Industrial automation.

CONSTRUCTION :

Cores	1.5 Pair (3 Cores)
Section	22 AWG
Conductor Material	Stranded tinned copper (TC)
Insulation	Polyethylene (PE)
Colour	White/Blue, Blue/ White
Pair	2 Cores twisted to a pair
Braiding	Tinned Copper wire
Screen (100% Coverage)	Aluminium/Polyester
Drain wire	Stranded Tinned Copper Wire
Rip Cord	Nylon Yarn
Sheath materials	Flame-Retardant Polyvinyl Chloride (PVC)
Sheath colour	Grey RAL 7001
Standard Put Up Length	305, 500 meters



PHYSICAL & MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-25°C to +75°C
Nominal Cable Weight (kg/km)	69
Nominal Insulation Thickness (mm)	0.6
Nominal Sheath Thickness (mm)	0.8
Nominal Overall Diameter (mm)	7.5
Min. Bend Radius (install) (mm)	75
Max. Pull Tension (N)	290

TECHNICAL DATA & STANDARD REFERENCES

(BS) EN 50290-2
UL 1581
IEC 60332-1-2, IEC 60332-1-3
IEC 60228
RoHS Directives

ELECTRICAL CHARACTERISTICS

Capacitance Cond. To Cond	36 pF/m
Capacitance Cond. To Screen.	69 pF/m
DC Resistance per core @ 20°C	57.8Ω/km
Max. Recommended Current @25°C	2.8 (Amps)
Nominal Impedance (Ω)	119
Nom. Velocity of Propagation	68 (%)
Operating Voltage	300 V (Vrms)

BELFAST ACCREDITED BY :

