



DESCRIPTION :


2 Core, 12 AWG Multi Conductor cable with Stranded Bare Copper (BC) conductors, PE insulation, Overall Shielded, PVC sheath for consistent performance, signal integrity, and EMI protection.

APPLICATION :

Multi-conductor cable suitable for building management systems (BMS), instrumentation, security, and audio control/sound system applications.

CONSTRUCTION :

Cores	2 Core
Section	12AWG
Conductor Material	Stranded Bare Copper (BC)
Insulation	Polyethylene (PE)
Colour	Black, White
Cabling	Cores laid by twisting
Screen (100% Coverage)	Aluminium/Polyester
Drain Wire	Stranded Tinned Copper Wire
Rip Cord	Nylon Yarn
Sheath Material	Flame-Retardant Polyvinyl Chloride (PVC)
Sheath Color	RAL 7001 (Grey)
Standard Put Up Length	305, 500 meters



PHYSICAL & MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-25°C to +75°C
Nominal Cable Weight (kg/km)	87
Nominal Insulation Thickness (mm)	0.4
Nominal Sheath Thickness (mm)	0.50
Nominal Overall Diameter (mm)	7.0
Min. Bend Radius (install) (mm)	70
Max. Pull Tension (N)	677

TECHNICAL DATA & STANDARD REFERENCES

(BS) EN 50290-2
UL 1581
IEC 60228, IEC 60332-1
RoHS Directives

ELECTRICAL CHARACTERISTICS

Capacitance Cond. To Cond.	106 pF/m
Capacitance Cond. To Screen.	219 pF/m
DC Resistance per core @ 20°C	5.60Ω/km
Max. DC Resistance Screen (Ω/km)	78.6
Recommended Current at 25°C	13 (Amps)
Inductance	0.5 μH/m
Operating Voltage	300 V (Vrms)

BELFAST ACCREDITED BY :

