



BCS14001FE

DESCRIPTION :


3 Core, 12 AWG multi-conductor cable with Stranded Bare Copper conductors, PE insulation, and overall shielding, LSZH/HFFR sheath for enhanced fire safety, low smoke, and zero halogen emissions.

APPLICATION :

Multi-conductor cable suitable for building management systems (BMS), instrumentation, security, and audio control/sound system applications.

CONSTRUCTION :

Cores	3 Core
Section	12AWG
Conductor Material	Stranded Bare Copper (BC)
Insulation	Polyethylene (PE)
Colour	Black, Red, White
Cabling	Cores laid by twisting
Screen (100% Coverage)	Aluminium/Polyester
Drain Wire	Stranded Tinned Copper Wire
Rip Cord	Nylon Yarn
Sheath Material	Low Smoke Zero Halogen (LSZH/ FRNC)
Sheath Color	RAL 4005 (Purple)
Standard Put Up Length	305, 500 meters



PHYSICAL & MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-25°C to +75°C
Nominal Cable Weight (kg/km)	132
Nominal Insulation Thickness (mm)	0.5
Nominal Sheath Thickness (mm)	0.57
Nominal Overall Diameter (mm)	7.2
Min. Bend Radius (install) (mm)	72
Max. Pull Tension (N)	677

TECHNICAL DATA & STANDARD REFERENCES

IEC 60228
EN 50290-2
IEC 60332-1, IEC 60754-1/2, IEC 61034-2
UL 1685
RoHS Directives

ELECTRICAL CHARACTERISTICS

Capacitance Cond. To Cond.	102 pF/m
Capacitance Cond. To Screen.	219 pF/m
DC Resistance Conductor (Ω/km)	5.60Ω/km
DC Resistance Screen (Ω/km)	78.5Ω/km
Max. Recommended Current at 25°C	12 (Amps)
Inductance	0.5 μH/m
Operating Voltage	300 V (Vrms)

BELFAST ACCREDITED BY :

