



BCS15501UE

DESCRIPTION :


3 Core, 22AWG Multi Conductor cable with Stranded Bare Copper (BC) conductors, PE insulation, Unshielded, PVC sheath for consistent performance, signal integrity, and EMI protection.

APPLICATION :

Multi-conductor cable suitable for building management systems (BMS), instrumentation, security, and audio control/sound system applications.

CONSTRUCTION :

Cores	3 Core
Section	22AWG
Conductor Material	Stranded Bare Copper (BC)
Insulation	Polyethylene (PE)
Colour	Black, Red, White
Cabling	Cores laid by twisting
Rip Cord	Nylon Yarn
Sheath Material	Flame-Retardant Polyvinyl Chloride (PVC)
Sheath Color	RAL 7001 (Grey)
Standard Put Up Length	305, 500 meters



PHYSICAL & MECHANICAL CHARACTERISTICS

Operating Temperature (°C)	-25°C to +75°C
Nominal Cable Weight (kg/km)	19
Nominal Insulation Thickness (mm)	0.22
Nominal Sheath Thickness (mm)	0.5
Nominal Overall Diameter (mm)	3.8
Min. Bend Radius (install) (mm)	38
Max. Pull Tension (N)	120

ELECTRICAL CHARACTERISTICS

Capacitance Cond. To Cond.	34 pF/m
DC Resistance per core @ 20°C	55.4Ω/km
Max. Recommended Current at 25°C	3.0 (Amps)
Inductance	0.5 μH/m
Operating Voltage	300 V (Vrms)

TECHNICAL DATA & STANDARD REFERENCES

(BS) EN 50290-2
IEC 60332-1
IEC 60228
UL 1581, RoHS Directives

BELFAST ACCREDITED BY :

